

## RCINGE12F8-MS Series Managed 12x 10/100/1000Base-T and 8x 1G (SFP) Ethernet Switch

The Rancent RCINGE12F8-MS is an Industrial Gigabit Managed Switch equipped with twelve 10/100/1000Mbps RJ45 ports and eight 1000M SFP (fiber) uplink ports that provide stable and reliable Ethernet transmission. For fast and efficient connectivity from the network edge device to a backbone switch or server, the managed Gigabit Ethernet switch is designed to extend existing LANs through one 1000Base-SX/LX/EX/BX SFP interface using either one or two multimode or singlemode fibers. The Industrial Managed Switches are fully managed Layer 2 switches not only incorporating the industry standard Rapid Spanning Tree Protocol (IEEE802.1w RSTP), but also a rapid ring recovery protocol enabling operational network recovery in the event of a network or power system failure.



### Typical Applications

- Any network utilizing a mix of copper and fiber
- Industrial IP connectivity and communication
- Self-healing Gigabit Ethernet backbone networks
- Networks using Ethernet devices such as network cameras, access control, intercoms, etc

### Product Features

- 12-Port 10/100/1000Base-T Gigabit Ethernet RJ-45 Ports
- 8-Port 1000Base-SX/LX/EX/BX SFP Type Slots
- Non-blocking store-and-forward switching
- RJ45 Port Supports 10/100/1000Mbps-Full/Half-duplex, Auto-negotiation, Auto MDI/MDIX
- Prevents Packet Loss w/Back Pressure (Half-Duplex) and IEEE 802.3x PAUSE Frame Flow Control (Full-Duplex)
- Available for operation in Ring or point-to-point configuration
- Available for operation over singlemode or multimode fiber over a variety of link budget
- Redundant dual power supply inputs 48/52 VDC
- 4KV Ethernet Surge Protection for harsh environment
- -40°C to 80°C (-40°F to 176°F) wide range operating temperature
- Real-time monitoring via Embedded Surveillance Device Management System
- Compact, corrosion resistant case attaches to a standard DIN Rails

# Specifications

## Physical Ports

Copper Ports (RJ45)	12 x 10/100/1000Base-T
SFP Uplink Ports	8 x 1000Base-SX/LX/EX/BX SFP
Port Configuration	Auto MDI/MDI-X
Port Speed	Auto-negotiate

## Ethernet

Switch Architecture	Store-and-forward
Switch Bandwidth	40Gbps (non-blocking)
MAC Address	8K entries
Maximum Frame Size	9.6K Bytes (Jumbo Frames)
Flow Control	Back pressure(Half-Duplex); IEEE 802.3x Pause Frame (Full-Duplex)

## Layer 2 Functions

Management Interface	Console, Cisco® like CLI,telnet, Web browser,SSH/SSL secure access, SNMPv1 and v2c and v3c
Port Configuration Port	enable/disable; Auto-negotiation; 10/100/1000Mbps full-and-half duplex mode selection; Flow control
Port Mirroring	TX/RX/Both; Many to 1 monitoring
Bandwidth Control	Ingress/Egress rate control: configure (100~1000000)Kbps Full Speed 1000000Kbps
VLAN	IEEE 802.1q tagged-based VLAN, up to 256 VLANs groups, out of 4094 VLAN IDs Port-based VLAN. Port-based VLAN, Q-in-Q tunneling, Mac-based VLAN, up to 256 VLANs Protocol-based VLAN, up to 128 VLANs MVR (Multiple VLAN Registration)
Link Aggregation	IEEE 802.3ad LACP / Static Trunk; Up to 5 groups of trunk supported
Quality of Service (QoS)	8 priority queue Traffic classification based on: IEEE802.1p Based Cos, IP DSCP Based Cos
Multicasting/IGMP	IGMP/MLD Snooping (v1,v2, v3) With Query supported
Access Control List	IP-Based ACL/MAC-Based ACL, 256 entries
SNMP MIBs	RFC-1213 MIB-II RFC-2819 RMON MIB (Group 1, 2, 3,9)

## Fiber

Data Rate	1000Base-SX/LX/EX/BX
Connector	SFP (Mini-GBIC) port
Fiber Type/Distance	Varies by SFP module

## LED Indicators & Switch

Power	On/Green
Ethernet	10/100 LNK/ACT - Amber; 1000 LNK/ACT - Green
SFP Ports	On/Blink - Green

## Electrical and Mechanical

Power Input Voltage	100~240VAC, 50/60Hz
Power Consumption	18 Watts
Dimensions	483x 280x 45mm
Case	IP30 Metal Case
Storage Temperature	-40°C~+80°C
Relative Humidity	0%~95% (non-condensing)

## Standards Compliance

Regulatory Standard	CE; FCC Part 15 Class A
IEEE/RFC Standards	
IEEE 802.3i	10Base-T
IEEE 802.3u	100Base-TX
IEEE 802.3ab	1000Base-T
IEEE 802.3z	1000Base-SX/LX
IEEE 802.3x	Flow Control and Back pressure
IEEE 802.1d	STP (Spanning Tree Protocol)
IEEE 802.1w	RSTP (Rapid Spanning Tree Protocol)
IEEE 802.1s	MSTP (Multiple Spanning Tree Protocol)
ITU-T G.8032/Y.1344 ERPS	(Ethernet Ring Protection Switch)
IEEE 802.1p	QoS/CoS Protocol for Traffic Prioritization
IEEE 802.1Q	VLAN Tagging
IEEE 802.1ad	Stacked VLAN,Q-in-Q
IEEE 802.1ab	LLDP(Link Layer Discovery Protocol)
IEEE 802.1X	Port Authentication Network Control
IEEE 802.3ad	Port trunk with LACP (Link Aggregation Control Protocol)
IEEE 802.3az	EEE (Energy Efficient Ethernet)
IEC Standards	
	IEC60068-2-32 (Free fall)
	IEC60068-2-27 (Shock)
	IEC60068-2-6 (Vibration)

# Dimensional Diagrams

